

UNCLASSIFIED

AD NUMBER

AD488321

LIMITATION CHANGES

TO:

Approved for public release; distribution is unlimited.

FROM:

Distribution authorized to U.S. Gov't. agencies and their contractors;
Administrative/Operational Use; JUL 1966. Other requests shall be referred to Air Force Armament Lab., Eglin AFB, OH 45433.

AUTHORITY

AFATL ltr 1 Aug 1977

THIS PAGE IS UNCLASSIFIED

THIS REPORT HAS BEEN DELIMITED
AND CLEARED FOR PUBLIC RELEASE
UNDER DOD DIRECTIVE 5200.20 AND
NO RESTRICTIONS ARE IMPOSED UPON
ITS USE AND DISCLOSURE,

DISTRIBUTION STATEMENT A

APPROVED FOR PUBLIC RELEASE,
DISTRIBUTION UNLIMITED,

488321

ATL-TR-66-59

Flight and Gun Setting for Side Firing Aircraft

by
Kenneth K. Cobb
and
Gerald Solomon

JULY 1966

This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of AFATL (ATB), Eglin Air Force Base, Florida.

**AIR FORCE ARMAMENT LABORATORY
RESEARCH AND TECHNOLOGY DIVISION
AIR FORCE SYSTEMS COMMAND
EGLIN AIR FORCE BASE, FLORIDA**

FLIGHT AND GUN SETTINGS FOR
SIDE FIRING AIRCRAFT

by
Kenneth K. Cobb
and
Gerald Solomon


This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of AFATL (ATB), Eglin Air Force Base, Florida.

FOREWORD

This report was prepared by Air Force Armament Laboratory (AFATL) (ATBR), Eglin Air Force Base, Florida, under Project 2547, "Advanced Non-Nuclear Weapon Ballistics". The preliminary work was furnished to several interested agencies in November 1965.

Information in this report is embargoed under the Department of State International Traffic In Arms Regulations. This report may be released to foreign governments by departments or agencies of the U. S. Government subject to approval of AFATL (ATB), Eglin Air Force Base, Florida, or higher authority within the Department of the Air Force. Private individuals or firms require a Department of State export license.

This technical report has been reviewed and is approved.


for CHARLES E. WOOD
Lt Col, USAF
Chief, Ballistics Division

ABSTRACT

This report provides information on the sighting of side firing guns for different gun declinations, slant ranges, and altitudes. The information was generated and provided for use in the employment of the AC-47 MINI-gun system and for the design of the follow-on installations.

BLANK PAGE

CONTENTS

	Page
GENERAL	1
DEFINITIONS	1
EXPLANATION OF CURVES	2
Figure	
CURVE SET I	5
1 True Airspeed Necessary to Have Gun Line on Center of Turn. Gun Declination 0°. Valid for All Slant Ranges	6
2 True Airspeed Necessary to Have Gun Line on Center of Turn. Gun Declination 5°	7
3 True Airspeed Necessary to Have Gun Line on Center of Turn. Gun Declination 10°	8
4 True Airspeed Necessary to Have Gun Line on Center of Turn. Gun Declination 12°	9
5 True Airspeed Necessary to Have Gun Line on Center of Turn. Gun Declination 14°	10
6 True Airspeed Necessary to Have Gun Line on Center of Turn. Gun Declination 16°	11
CURVE SET II	13
7 True Airspeed Necessary to Have Gun Line on Center of Turn. Slant Range 3000 Ft	14
8 True Airspeed Necessary to Have Gun Line on Center of Turn. Slant Range 4000 Ft	15
9 True Airspeed Necessary to Have Gun Line on Center of Turn. Slant Range 4500 Ft	16
10 True Airspeed Necessary to Have Gun Line on Center of Turn. Slant Range 5000 Ft	17
11 True Airspeed Necessary to Have Gun Line on Center of Turn. Slant Range 6000 Ft	18
CURVE SET III	19
12 True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 0°, Slant Range 3000 Ft	20
13 True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 0°, Slant Range 4000 Ft	21
14 True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 0°, Slant Range 4500 Ft	22
15 True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 0°, Slant Range 5000 Ft	23
16 True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 0°, Slant Range 6000 Ft	24

17	True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 10°, Slant Range 3000 Ft 25
18	True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 10°, Slant Range 4000 Ft 26
19	True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 10°, Slant Range 4500 Ft 27
20	True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 10°, Slant Range 5000 Ft 28
21	True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 10°, Slant Range 6000 Ft 29
22	True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 12°, Slant Range 3000 Ft 30
23	True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 12°, Slant Range 4000 Ft 31
24	True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 12°, Slant Range 4500 Ft 32
25	True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 12°, Slant Range 5000 Ft 33
26	True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 12°, Slant Range 6000 Ft 34
27	True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 14°, Slant Range 3000 Ft 35
28	True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 14°, Slant Range 4000 Ft 36
29	True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 14°, Slant Range 4500 Ft 37
30	True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 14°, Slant Range 5000 Ft 38
31	True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 14°, Slant Range 6000 Ft 39
	CURVE SET IV	41
32	Angle of Bank for Constant Slant Range, Altitude 2500 Ft, Airspeed 130 Kt	42
33	Angle of Bank for Constant Slant Range, Altitude 2500 Ft, Airspeed 140 Kt	43
34	Angle of Bank for Constant Slant Range, Altitude 2500 Ft, Airspeed 150 Kt	44
35	Angle of Bank for Constant Slant Range, Altitude 2500 Ft, Airspeed 160 Kt	45
36	Angle of Bank for Constant Slant Range, Altitude 3000 Ft, Airspeed 130 Kt	46
37	Angle of Bank for Constant Slant Range, Altitude 3000 Ft, Airspeed 140 Kt	47
38	Angle of Bank for Constant Slant Range, Altitude 3000 Ft, Airspeed 150 Kt	48

39	Angle of Bank for Constant Slant Range, Altitude 3000 Ft, Air-speed 160 Kt	49
40	Angle of Bank for Constant Slant Range, Altitude 3500 Ft, Air-speed 130 Kt	50
41	Angle of Bank for Constant Slant Range, Altitude 3500 Ft, Air-speed 140 Kt	51
42	Angle of Bank for Constant Slant Range, Altitude 3500 Ft, Air-speed 150 Kt	52
43	Angle of Bank for Constant Slant Range, Altitude 3500 Ft, Air-speed 160 Kt	53
44	Angle of Bank for Constant Slant Range, Altitude 4000 Ft, Air-speed 130 Kt	54
45	Angle of Bank for Constant Slant Range, Altitude 4000 Ft, Air-speed 140 Kt	55
46	Angle of Bank for Constant Slant Range, Altitude 4000 Ft, Air-speed 150 Kt	56
47	Angle of Bank for Constant Slant Range, Altitude 4000 Ft, Air-speed 160 Kt	57
48	Angle of Bank for Constant Slant Range, Altitude 5000 Ft, Air-speed 130 Kt	58
49	Angle of Bank for Constant Slant Range, Altitude 5000 Ft, Air-speed 140 Kt	59
50	Angle of Bank for Constant Slant Range, Altitude 5000 Ft, Air-speed 150 Kt	60
51	Angle of Bank for Constant Slant Range, Altitude 5000 Ft, Air-speed 160 Kt	61

BLANK PAGE

GENERAL

The AC-47 MINI-gun system, as originally designed, was aimed nearly parallel to the lateral (wing line) of the aircraft. It was suggested in AMR 65-36 (September 1965) that for the desired firing conditions (altitude, true airspeed, and slant range) of the system, the aiming and maneuvering of the aircraft would be simplified by declinating the guns in order to put the gun line near the center of the turn. The required declination depends primarily on the aircraft altitude above ground level, the true airspeed, and to some extent, on the slant range. See figure on page 3. For the firing conditions of the AC-47 aircraft, a declination of about 13° is required.

A gun stand declination device was designed by Lt. Col. Lloyd Combs of SAWC in December 1965. Two gun pods were boresighted on a single aircraft which had the declinated stands set at 12° down. Capt. Lowell Kirkpatrick, who has considerable experience firing the gun from non-declinated stands, flew the missions to evaluate the system with declinated guns. He reported that the declinated gun system was easier to fly and it was more accurate. There was no difficulty in sighting the target.

Presently, the module (follow-on AC-47 gun stand) is being tested by APGC at Eglin AFB. A screw mechanism was added to this system to facilitate gun declination to 18° . One purpose of the module test is to establish the optimum declination angle for given firing conditions.

This report gives curves and data on the sighting and flight characteristics for the MINI-gun side firing aircraft for different gun declinations, slant ranges, and altitudes. These data were generated as indicated in Appendix I.

DEFINITIONS

1. Bank Angle (θ) - The vertical angle from the horizontal to the wing line, lateral axis of aircraft.
2. Center Angle (ϕ) - The vertical angle from the horizontal to the center of the turn.
3. Gun Line - A line perpendicular to the longitudinal axis of the aircraft and in the declinated lateral plane of the gun.
4. Gun Angle (ϕ_g) - The vertical angle from the horizontal to the gun line, lateral plane of gun.
5. Slant Range (SR) - The line distance from the aircraft to the target.

EXPLANATION OF CURVES

Curve Set I (Figures 1 - 6) gives the true airspeed necessary to bring the gun line on the center of the turn for declination angles of 0° , 5° , 10° , 12° , 14° , and 16° . For each gun declination angle except 0° there is a slight dependence on slant range. For 0° gun declination the true airspeed necessary to keep the guns on the center of the turn depends only on the altitude above ground level.

From the curves it is seen that a gun declination of 14° gives good performance. This allows the pilot to keep the guns nearly on the center of the turn between altitudes (AGL) of 2000 to 4000 ft by varying the true airspeed between 100 and 164 kt. The gun declination provides a gun line slightly above the center of the turn and allows for a drop of about 1.25° (22 mils) for the following conditions: altitude 3000 ft, TAS 142 kt, gun angle 42° and bank angle of 28° . For the original AC-47 system, the sighting point on the boresight frame was set for 130 kt. If the guns are fired at an airspeed exceeding that for which they were boresighted the sighting point must be moved forward about .625 mil/kt.

Curve Set II (Figures 7 - 11) gives the same data as the first set. In Set II each figure is for a given slant range with different curves representing gun declination of 0° , 5° , 10° , 12° , 14° , 16° , and 20° .


Curve Set III (Figures 12 - 31) are useful once the guns are fixed. This set gives the true airspeed necessary to bear the guns or the sight on the center of the turn for a given gun declination. The top (solid) line gives the true airspeed necessary to keep the gun line on the target (center of turn). The lower dashed line gives the true airspeed to keep the guns above the center of the turn by the amount of the projectile drop. That is, for each altitude there is a fixed gun angle for the fixed slant range. The sight is declinated below the gun line by the amount of the gravity drop at each altitude. The lower (dashed) curve then gives the true airspeed to keep the sight on center of the turn (target).

The true airspeed is plotted versus altitude AGL. The altitude AGL corresponds to a set bank angle (and gun angle) for the given slant range and gun declination. Also plotted, along the abscissa of the curve, are the gun angle, the bank angle corresponding to the altitude, the slant range to the target and the mil drop corresponding to the slant range and gun angle.

An example of the use of Curve Set III follows: Suppose the gun declination is 12° , and the pilot desires to open fire at 4500 ft SR from 3000 ft AGL (see Figure 24, reading under 3000 ft). We find a bank angle of about 30° , a gun angle of about 42° , and a mil drop of about 22 mils. Reading up to the dashed

curve, we find a true airspeed of 144 kt. With this bank angle, altitude, and true airspeed, the aim point is at the center of the turn and the guns are slightly above the center of the turn to account for the projectile drop. It is assumed that the sight is declinated below the gun line to account for the gravity drop.

Curve Set IV (Figures 32 - 51) shows the required bank angle to keep the slant range to the center of the turn constant for a given true airspeed and altitude above ground level. The dashed curve in this curve set gives the angle from the horizontal to the center of the turn. The two upper solid curves give the angle from the horizontal to the gun line for specified declination angles. Refer to figure below.



CONSIDERING FORCES ON AIRCRAFT AND GEOMETRY FOR LEVEL TURN. IT CAN BE SHOWN

$$\tan \theta = \frac{v^2}{gA} \quad \tan \phi = \frac{v^2}{gA} \left(\frac{SR^2}{A^2} - 1 \right)^{\frac{1}{2}}$$

V = SPEED OF AIRCRAFT

Physical Characteristics for Side Firing Aircraft.

BLANK PAGE

CURVE SET I




Figure 1. True Airspeed Necessary to Have Gun Line on Center of Turn, Gun Declination 0°. Valid for All Slant Ranges.




Figure 2. True Airspeed Necessary to Have Gun Line on Center of Turn, Gun Declination 5°.




Figure 3. True Airspeed Necessary to Have Gun Line on Center of Turn.
Gun Declination 10°.




Figure 4. True Airspeed Necessary to Have Gun Line on Center of Turn. Gun Declination 12°.




Figure 5. True Airspeed Necessary to Have Gun Line on Center of Turn, Gun Declination 14° .




Figure 6. True Airspeed Necessary to Have Gun Line on Center of Turn.
Gun Declination 16°.

BLANK PAGE

CURVE SET II




Figure 7. True Airspeed Necessary to Have Gun Line on Center of Turn. Slant Range 3000 Ft.




Figure 8. True Airspeed Necessary to Have Gun Line on Center of Turn. Slant Range 4000 Ft.




Figure 9. True Airspeed Necessary to Have Gun Line on Center of Turn, Slant Range 4500 Ft.




Figure 10. True Airspeed Necessary to Have Gun Line on Center of Turn, Slant Range 5000 Ft.




Figure 11. True Airspeed Necessary to Have Gun Line on Center of Turn. Slant Range 6000 Ft.

CURVE SET I.I




Figure 12. True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 0° , Slant Range 3000 Ft.




Figure 13. True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 0° , Slant Range 4000 Ft.




Figure 14. True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 0° , Slant Range 4500 Ft.




Figure 15. True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 0° , Slant Range 5000 Ft.




Figure 16. True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 0° , Slant Range 6000 Ft.




Figure 17. True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 10° , Slant Range 3000 Ft.




Figure 18. True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 10° , Slant Range 4000 Ft.




Figure 19. True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 10° , Slant Range 4500 Ft.




Figure 20. True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 10° , Slant Range 5000 Ft.




Figure 21. True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 10° , Slant Range 6000 Ft.




Figure 22. True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 12° , Slant Range 3000 Ft.




Figure 23. True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 12° , Slant Range 4000 Ft.




Figure 24. True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 12° , Slant Range 4500 Ft.




Figure 25. True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 12° , Slant Range 5000 Ft.




Figure 26. True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 12° , Slant Range 6000 Ft.




Figure 27. True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 14° , Slant Range 3000 Ft.




Figure 28. True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 14° , Slant Range 4000 Ft.




Figure 29. True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 14° , Slant Range 4500 Ft.




Figure 30. True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 14° , Slant Range 5000 Ft.




Figure 31. True Airspeed Necessary to Have Gun Line and Sight Line on Center of Turn. Gun Declination 14° , Slant Range 6000 Ft.

BLANK PAGE

CURVE SET IV




Figure 32. Angle of Bank for Constant Slant Range, Altitude 2500 Ft, Airspeed 130 Kt.




Figure 33. Angle of Bank for Constant Slant Range, Altitude 2500 Ft, Airspeed 140 Kt.




Figure 34. Angle of Bank for Constant Slant Range, Altitude 2500 Ft, Airspeed 150 Kt.




Figure 35. Angle of Bank for Constant Slant Range, Altitude 2500 Ft, Airspeed 160 Kt.




Figure 36. Angle of Bank for Constant Slant Range, Altitude 3000 Ft, Airspeed 130 Kt.




Figure 37. Angle of Bank for Constant Slant Range, Altitude 3000 Ft, Airspeed 140 Kt.




Figure 38. Angle of Bank for Constant Slant Range, Altitude 3000 Ft, Airspeed 150 Kt.




Figure 39. Angle of Bank for Constant Slant Range, Altitude 3000 Ft, Airspeed 160 Kt.




Figure 40. Angle of Bank for Constant Slant Range, Altitude 3500 Ft, Airspeed 150 Kt.




Figure 41. Angle of Bank for Constant Slant Range, Altitude 3500 Ft, Airspeed 140 Kt.




Figure 42. Angle of Bank for Constant Slant Range, Altitude 3500 Ft, Airspeed 150 Kt.




Figure 43. Angle of Bank for Constant Slant Range, Altitude 3500 Ft, Airspeed 160 Kt.




Figure 44. Angle of Bank for Constant Slant Range, Altitude 4000 Ft, Air-speed 150 Kt.




Figure 45. Angle of Bank for Constant Slant Range, Altitude 4000 Ft, Airspeed 140 Kt.




Figure 46. Angle of Bank for Constant Slant Range, Altitude 4000 Ft, Airspeed 150 Kt.




Figure 47. Angle of Bank for Constant Slant Range, Altitude 4000 Ft, Airspeed 160 Kt.




Figure 48. Angle of Bank for Constant Slant Range, Altitude 5000 Ft, Airspeed 130 Kt.




Figure 49. Angle of Bank for Constant Slant Range, Altitude 5000 Ft, Airspeed 140 Kt.




Figure 50. Angle of Bank for Constant Slant Range, Altitude 5000 Ft, Airspeed 150 Kt.




Figure 51. Angle of Bank for Constant Slant Range, Altitude 5000 Ft, Airspeed 160 Kt.

BLANK PAGE

APPENDIX I

EQUATIONS (SEE FIGURE ON PAGE 3).

It is shown in Bibliography 1 that the relationship between the bank angle θ and the angle to the center of turn ϕ for an aircraft in a level turn is given by,

$$\tan \theta = (V^2/gA) (\tan \phi) \quad (I-1)$$

Where:

θ = Bank angle from the horizontal to the wing line (lateral axis of the aircraft)

ϕ = Angle from the horizontal to the center of the turn

V = TAS of the aircraft

A = Aircraft altitude AGL

Equation (I-1) may be rewritten as

$$V = \left(gA \frac{\tan \theta}{\tan \phi} \right)^{\frac{1}{2}} \quad (I-2)$$

which gives the airspeed necessary to fly at an altitude A , and bank angle θ , with the center of the turn at an angle ϕ from the horizontal. The relationship between the slant range SR , the altitude A , and the angle ϕ are as follows:

$$SR = A/\sin \phi \quad (I-3)$$

or

$$\phi = \sin^{-1} \frac{A}{SR}$$

The declination angle ψ is defined as the angle from the lateral axis of the aircraft (wing line) to the lateral plane containing the gun. From this definition $\theta = \phi - \psi$. (I-4)

CURVE SET I

In this curve set, the gun declination Ψ is fixed for each graph. For a given slant range and altitude, the angle to the center of turn (target) ϕ is obtained from equation (I-3). Then the bank angle θ is obtained from (I-4). θ , ϕ , and A are now substituted into equation (I-2) to obtain the true airspeed required to keep the guns bearing on the center of turn for a given gun declination, slant range, and altitude AGL. In each graph the true airspeed is plotted on the ordinate and the altitude AGL is plotted on the abscissa.

CURVE SET II

Each graph in this curve set has a fixed SR. The curves are generated using the same equations as in set I (i.e., the SR, altitude, and gun declination is set and the TAS necessary to keep the guns bearing on the target is then computed).

CURVE SET III

Each graph in Curve Set III represents a fixed condition of slant range and gun declination. The top solid curve is identical to those of Curve Set I, representing the given slant range. The lower dashed curve is obtained by adding the gravity drop to the angle ϕ and recomputing V from equation (I-2) for each value of θ and A . Specifically replace ϕ by

$$\phi' = \phi + \delta(\phi, SR) \quad (I-5)$$

Where ϕ is given by equation (I-3), and

δ = Gravity drop, and is a function of ϕ and the slant range.

The lower curves then give the airspeed necessary to keep the sight on the target with the sight declinated below the guns by an amount equal to the gravity drop.

CURVE SET IV

In each chart of Curve Set IV, the altitude and airspeed is fixed. In this set the abscissa gives the slant range to the target. The dashed curve gives the angle ϕ to the target (center of turn) by equation (I-3). The lower curve gives the bank angle necessary to remain at the corresponding constant

slant range (equation I-1). The two higher curves give the angular position of the gun ϕ_g with respect to the horizontal for the two declination angles 10° and 14° . They are obtained by simple adding 10° and 14° to the lower curve.

BIBLIOGRAPHY

1. "Aiming Considerations for Side Firing Aircraft Using Fixed Guns," Armament Memorandum Report 65-36, September 1965, AFATL, Eglin AFB, Florida, by Kenneth K. Cobb.
2. "Gun Settings for Side Firing Aircraft - 7.62 Minigun," Armament Memorandum Report 65-24, July 1965, AFATL, Eglin AFB, Florida, by Kenneth K. Cobb.

UNCLASSIFIED

Security Classification

DOCUMENT CONTROL DATA - R&D		
(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)		
1 ORIGINATING ACTIVITY (Corporate author) Air Proving Ground Center Eglin Air Force Base, Florida		2a REPORT SECURITY CLASSIFICATION Unclassified
		2b GROUP --
3 REPORT TITLE Flight and Gun Settings for Side Firing Aircraft		
4 DESCRIPTIVE NOTES (Type of report and inclusive dates) Final report (Nov 65)		
5 AUTHOR(S) (Last name, first name, initial) Cobb, Kenneth K. Solomon, Gerald		
6 REPORT DATE July 1966	7a TOTAL NO. OF PAGES 76	7b NO. OF REFS --
8a CONTRACT OR GRANT NO. b. PROJECT NO. 2547 c. d.	9a. ORIGINATOR'S REPORT NUMBER(S) ATL-TR-66-59 9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
10. AVAILABILITY/LIMITATION NOTICES Available in DDC. This document is subject to special export controls and each transmittal to foreign governments or foreign nationals may be made only with prior approval of AFATL (ATB), Eglin AFB, Florida.		
11. SUPPLEMENTARY NOTES	12. SPONSORING MILITARY ACTIVITY Air Force Armament Laboratory Research and Technology Division	
13 ABSTRACT This report provides information on the sighting of side firing guns for different gun declinations, slant ranges, and altitudes. The information was generated and provided for use in the employment of the AC-47 MINI-gun system and for the design of the follow-on installations.		

DD FORM 1473
1 JAN 64

UNCLASSIFIED

Security Classification

UNCLASSIFIED

Security Classification

14 KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Aerial Gunnery Aerodynamic Configuration Aiming Circles Aircraft Guns Automatic Weapons Ballistics Fire Control Systems Guns Lead Angle Projectile Trajectories						

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).

10. **AVAILABILITY LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.

UNCLASSIFIED

Security Classification

SUPPLEMENTARY

INFORMATION

ERRATA

AD-488 321
ATL-TR-66-59. Flight and Gun Setting for Side Firing Aircraft. July 1966. Unclassified Report. Air Force Armament Laboratory (RTD) (AFSC), Eglin Air Force Base, Florida.

Change the exponent () ^{$\frac{1}{2}$} to () ^{$-\frac{1}{2}$} (Note: minus one-half) in the equation on page 3.